


# AS 504

<b>TIRE SIZE</b>	<b>400/80 - 24</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
<b>VERSION</b>	INDUSTRIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	156 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94035588	<b>RC (IN)</b>	143.9
<b>SW (IN)</b>	15.5	<b>RIM REC</b>	W 13
<b>OD (IN)</b>	49.7	<b>RIM ALT</b>	W 12; W 14 L
<b>SLR (IN)</b>	22.3		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	55
5	11020
15	9350
20	9170
25	8820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.