


# AGRIMAX FORCE

<b>TIRE SIZE</b>	<b>IF 650/85 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	КОМБАЙН / ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	180 D



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94046904	<b>RC (IN)</b>	252.0
<b>SW (IN)</b>	25.6	<b>RIM REC</b>	DW 23 B
<b>OD (IN)</b>	85.6	<b>ECE</b>	E4-106R-001832
<b>SLR (IN)</b>	38.0	<b>TRA CODE</b>	R1W

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	7540	8660	9940	11230	12510	13800	15080	16050
<b>FROM 40 TO 25</b>	8290	9520	10930	12350	13760	15170	16580	17600
20	8620	9900	11360	12830	14300	15770	17240	18340
12	8950	10280	11810	13330	14850	16380	17900	19050
5	10530	12090	13880	15670	17460	19260	21050	22400
<b>UPTO 20 CYC</b>	10770	12380	14210	16050	17880	19710	21550	22930
<b>UPTO 10 CYC</b>	12840	14760	16940	19140	21320	23500	25690	27340
<b>UPTO 5 CYC</b>	14090	16180	18580	20990	23380	25780	28170	29980
5 HT	8620	9900	11360	12830	14300	15770	17240	18340

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.