

# LG 306

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 26X12.00 - 12                            |
| <b>UM</b>           | IS STANDARD                              |
| <b>CONSTRUCTION</b> | BIAS                                     |
| <b>MACHINERY</b>    | ÅKGRÄSKLIPPARE / LITEN TRAKTOR / TRAKTOR |
| <b>VERSION</b>      | ARAMID BELTED                            |
| <b>TIRE TYPE</b>    | TL                                       |



## DIMENSIONER IS STANDARD

|                 |      |                |                              |
|-----------------|------|----------------|------------------------------|
| <b>SW (MM)</b>  | 310  | <b>RIM REC</b> | 10.50 I - 55; I - 70; I - 90 |
| <b>OD (MM)</b>  | 640  | <b>RIM ALT</b> | 10½ JA; 8½ JA                |
| <b>SLR (MM)</b> | 283  | <b>ECE</b>     | E11-106R-003384              |
| <b>RC (MM)</b>  | 1856 | <b>PR</b>      | 6                            |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.10</b> |
| 15                | 1030        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.