DATA SHEET

Latest update
2-06-2026

AGRIMAX RT 855

TYRE SIZE	**460/85 R 34**
UM	US STANDARD
CONSTRUCTION	RADIAL
MACHINERY	SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS
VERSION	STANDARD
TL/TT	TL
LI/SS	147 A8/B

DIMENSIONS US STANDARD

USA CODE	94021772	**RC (IN)**	191.5
SW (IN)	18.7	**RIM REC**	W 16 L
OD (IN)	64.8	**RIM ALT**	W 14 L ; W 15 L
SLR (IN)	28.4	**ECE**	E4-106R-000632

LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23
30	3740	4340	4950	5570	6170	6780
25	3740	4340	4950	5570	6170	6780
20	4000	4650	5310	5960	6610	7260
5 LT	5000	5820	6650	7460	8280	9090
5 HT	4000	4650	5310	5960	6610	7260

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..