

# RIDEMAX FL 690

<b>TIRE SIZE</b>	VF 900/65 R 32
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	TANKER / TRAILER / IMPLEMENTS / TRAILER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	197 D



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	930	<b>RIM REC</b>	DW 31 B
<b>OD (MM)</b>	1986	<b>RIM ALT</b>	DW 30; TW 30
<b>SLR (MM)</b>	838	<b>ECE</b>	E11-106R-006917
<b>RC (MM)</b>	5878	<b>SRI</b>	925

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8
70	5030	6435	7840	8890	10295	11695
65	5530	7070	8610	9770	11310	12850
50	6470	8270	10075	11430	13235	15035
40	7130	9120	11110	12605	14595	16580
10	9065	11595	14125	16020	18550	21075

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.