

# LG 306

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 29X12.50 - 15  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> | BIAS   |
| <b>MACHINERY</b>    | MAQUINA DE CORTAR RELVA / TRATOR<br>PEQUENO / TRATOR |
| <b>VERSÃO</b>       | ARAMID BELTED  |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 113 B  |



## DIMENSÕES IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 318  | <b>RIM REC</b> | 10 LB           |
| <b>OD (MM)</b>  | 740  | <b>ECE</b>     | E11-106R-006167 |
| <b>SLR (MM)</b> | 349  | <b>PR</b>      | 10              |
| <b>RC (MM)</b>  | 2230 |                |                 |

## LOAD CAPACITY (KG/TIRE)

|                   |            |
|-------------------|------------|
| <b>KM/H / BAR</b> | <b>4.1</b> |
| 50                | 1150       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.