


# AGRIMAX RT 657

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>440/65 R 28</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | КОМБАЙН ДЛЯ УБОРКИ<br>ВИНОГРАДА / ТРАКТОР-ТЯГАЧ /<br>КОМБАЙН                             |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 138 D ; 141 A8   |



## РАЗМЕРЫ US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94029143 | <b>RC (IN)</b> | 154.6          |
| <b>SW (IN)</b>  | 17.4     | <b>RIM REC</b> | W 14 L         |
| <b>OD (IN)</b>  | 50.5     | <b>RIM ALT</b> | W 13; W 15 L   |
| <b>SLR (IN)</b> | 23.2     | <b>ECE</b>     | E4-106R-000767 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9    | 12   | 15   | 17   | 20   | 23   | 29   | 35   |
|-----------|------|------|------|------|------|------|------|------|
| 40        | 2500 | 2920 | 3280 | 3650 | 4010 | 4320 | 4790 | 5200 |
| 30        | 2630 | 3060 | 3450 | 3840 | 4210 | 4540 | 5040 | 5470 |
| 25        | 2730 | 3190 | 3580 | 3980 | 4380 | 4720 | 5220 | 5680 |
| 20        | 2880 | 3360 | 3780 | 4200 | 4620 | 4970 | 5510 | 5990 |
| 5 LT      | 3350 | 3910 | 4400 | 4890 | 5380 | 5800 | 6430 | 6980 |
| 5 HT      | 2880 | 3360 | 3780 | 4200 | 4620 | 4970 | 5510 | 5990 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.