

SNOW - RIDE (A)



SNOW - RIDE (A)



SNOW-RIDE is particularly suitable for municipality and maintenance applications in winter conditions with compact loaders and skid steers. It features excellent traction and is ideal for ice and snow operations. Its specially designed tread pattern eliminates slippage risks and ensures a longer tire life-cycle.



	SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
										
Ø16"	12.5/70 -16	-	10 LB	-	12.4	33.5	15.2	100.4	-	STD
	12.5/70 -16	-	10 LB	-	12.4	33.5	15.2	100.4	-	STD
Ø16.5"	12 - 16.5	-	9.75	-	12.0	32.9	14.9	98.6	-	STD
	10 - 16.5	-	8.25	-	10.6	30.7	14.1	92.1	-	STD
	12 - 16.5	-	9.75	-	12.0	32.9	14.9	98.6	-	STD

STD: STANDARD

TECHNOLOGIES		PERFORMANCES	
			 
			
-	-		

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026

	SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
										
	10 - 16.5	-	8.25	-	10.6	30.7	14.1	92.1	-	STD
Ø18"	15.5/60 -18	-	W 13	-	15.6	36.9	16.7	110.8	-	STD
Ø20"	17.5/65 -20	-	W 14 L	-	17.5	43.1	19.1	123.0	-	STD

STD: STANDARD

TECHNOLOGIES		PERFORMANCES	
			 
			
-	-		

Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index