

# EARTHMAX SR 53

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>26.5 R 25</b>                           |
| <b>UM</b>           | US STANDARD                                |
| <b>CONSTRUCTION</b> |  |
| <b>MACHINERY</b>    | DOZER / LOADER / LOW PROFILE<br>DUMP TRUCK |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND                     |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 202 A2                                     |



## DIMENSIONS US STANDARD

|                 |          |                    |           |
|-----------------|----------|--------------------|-----------|
| <b>USA CODE</b> | 94049103 | <b>RIM REC</b>     | 22.00/3.0 |
| <b>OD (IN)</b>  | 70.4     | <b>TRA CODE</b>    | L5        |
| <b>SLR (IN)</b> | 31.5     | <b>STAR RATING</b> | ★         |
| <b>RC (IN)</b>  | 211.7    |                    |           |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 58    | 62    | 65    | 69    | 73    |
|-----------|-------|-------|-------|-------|-------|
| 5         | 28300 | 29100 | 30900 | 32000 | 33100 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.