

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>210/95 R 20</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	BESPRUTNINGSBIL / SKÖRDEMASKIN FÖR VINGÅRD / TRAKTOR / SKÖRDEMASKIN / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	110 A8/B



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94043804	<b>RC (IN)</b>	108.2
<b>SW (IN)</b>	8.4	<b>RIM REC</b>	W 7
<b>OD (IN)</b>	35.7	<b>RIM ALT</b>	W 6
<b>SLR (IN)</b>	16.5	<b>ECE</b>	E4-106R-000637

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
<b>30</b>	1100	1270	1450	1640	1830	2020	2180	2340
<b>25</b>	1100	1270	1450	1640	1830	2020	2180	2340
<b>20</b>	1180	1360	1550	1750	1960	2160	2340	2500
<b>5 LT</b>	1480	1700	1950	2200	2460	2710	2930	3140
<b>5 HT</b>	1180	1360	1550	1750	1960	2160	2340	2500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.