

# AW 702

|                           |   |
|---------------------------|---|
| <b>TYRE SIZE</b>          | 11.5/80 - 15.3  |
| <b>UM</b>                 | IS STANDARD   |
| <b>CONSTRUCTION</b>       | ⊠ BIAS  |
| <b>MACHINERY</b>          | IMPLEMENT MACHINERY / TRAILER /<br>IMPLEMENTS / TRAILER |
| <b>VERSION</b>            | STANDARD  |
| <b>TYRE TYPE</b>          | TL  |
| <b>LI/SS FREE ROLLING</b> | 141 A8  |



## DIMENSIONS IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 297  | <b>RIM REC</b> | 9.00           |
| <b>OD (MM)</b>  | 844  | <b>ECE</b>     | E4-106R-002752 |
| <b>SLR (MM)</b> | 370  | <b>PR</b>      | 16             |
| <b>RC (MM)</b>  | 2473 |                |                |

## LOAD CAPACITY (KG/TYRE)

| <b>KM/H / BAR</b> | <b>5.40</b> |
|-------------------|-------------|
| 10 FR             | 3605        |
| 25 FR             | 3065        |
| 30 FR             | 2885        |
| 40 FR             | 2575        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.