

AT 171

| | |
|---------------------|--|
| TIRE SIZE | 38X10 - 20 |
| UM | US STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | ВЕЗДЕХОД / ТРАКТОР ДЛЯ ЕЗДЫ ПО ГРЯЗИ / ТРАКТОР-ТЯГАЧ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 93 A8 ; 69 F |



РАЗМЕРЫ US STANDARD

| | | | |
|-----------------|----------|----------------|-------|
| USA CODE | 94055180 | RC (IN) | 111.6 |
| SW (IN) | 9.3 | RIM REC | W 8 |
| OD (IN) | 37.4 | RIM ALT | W 7 |
| SLR (IN) | 17.4 | PR | 6 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 20 | 15 |
|---------------------|------|------|
| 25 MUD BOGGING | 1433 | - |
| 50 MUD BOGGING | 715 | - |
| 25 CASUAL TRANSPORT | - | 1170 |
| 50 CASUL TRANSPORT | - | 585 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.