DATA SHEET

PRINTED ON
21-04-2026

AGRIMAX RT 765

TYRE SIZE	**420/70 R 24**
UM	IS STANDARD
CONSTRUCTION	RADIAL
MACHINERY	TRACTOR / IMPLEMENTS
VERSION	SPECIAL
TYRE TYPE	TL
LI/SS	134 D

DIMENSIONS IS STANDARD

SW (MM)	418	**RIM REC**	W 13
OD (MM)	1248	**RIM ALT**	W 12; W 14 L
SLR (MM)	554	**ECE**	E11-106R-005825
RC (MM)	3680	**SRI**	600

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
65	1060	1230	1400	1590	1760	1930	2120
50	1115	1295	1475	1675	1855	2030	2230
40	1165	1350	1535	1745	1930	2120	2325
30	1220	1420	1615	1830	2030	2225	2440
10 LT	1425	1655	1880	2135	2365	2590	2845
10 HT	1220	1420	1615	1830	2030	2225	2440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..