


# AGRIMAX TURF RT 333

<b>TIRE SIZE</b>	<b>380/70 R 24</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRAUBENERNTEMASCHINE / ERNTEMASCHINE FÜR OBST / KLEINTRAKTOR / TRACTOR / ERNTEMASCHINE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	125 A8 ; 125 B



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94068838	<b>RC (IN)</b>	139.3
<b>SW (IN)</b>	15.0	<b>RIM REC</b>	W 12
<b>OD (IN)</b>	46.9	<b>RIM ALT</b>	W 11; W 13
<b>SLR (IN)</b>	21.0	<b>ECE</b>	E11-106R-007112

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	2010	2340	2660	2990	3320	3640
25	2010	2340	2660	2990	3320	3640
20	2150	2510	2860	3210	3570	3910
5 LT	2690	3140	3580	4020	4460	4890
5 HT	2150	2510	2860	3210	3570	3910

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.