

# LG 408

|                     |   |
|---------------------|---|
|                     | <b>24X13.00 - 12</b>                          |
| <b>UM</b>           | US STANDARD                                   |
| <b>CONSTRUCTION</b> | BIAS  |
| <b>MACHINERY</b>    | BIÇME MAKINELERİ / KÜÇÜK TRAKTÖR<br>/ TRAKTÖR |
| <b>VERSION</b>      | STANDARD                                      |
| <b>TIRE TYPE</b>    | TL  |



## UNDEFINED US STANDARD

|                 |          |                |                             |
|-----------------|----------|----------------|-----------------------------|
| <b>USA CODE</b> | 94012879 | <b>RC (IN)</b> | 69.1                        |
| <b>SW (IN)</b>  | 12.8     | <b>RIM REC</b> | 10.5 I - 55; I - 70; I - 90 |
| <b>OD (IN)</b>  | 24.0     | <b>ECE</b>     | E11-106R-003464             |
| <b>SLR (IN)</b> | 10.6     | <b>PR</b>      | 6                           |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>32</b> |
| 10               | 2390      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.