


MULTIMAX MP 527

TIRE SIZE	400/70 R 24 IND
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	KOMPAKTHJULLASTARE / TELESKOPLASTARE / KOMPAKTHJULLASTARE / TELESKOPLASTARE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	152 A8/B



DIMENSIONER IS STANDARD

SW (MM)	404	RIM REC	13
OD (MM)	1170	RIM ALT	DW 12 ; DW 13 ; DW 13 L ; 13 SDC ; DW 14 L
SLR (MM)	542	ECE	E11-106R-003958
RC (MM)	3597	SRI	575

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	1705	2025	2310	2630	2950	3160	3550	-	-
40	1705	2025	2310	2630	2950	3160	3550	-	-
30	1825	2170	2470	2815	3155	3385	3800	-	-
25	1895	2250	2565	2920	3275	3515	3945	-	-
10 CYC.	2080	2560	3010	3465	3945	4290	4850	5115	5325
STATIC	3185	3920	4615	5310	6045	6575	7435	7840	8165

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.