

RT 857



RT 857



RT 857 is a tyre designed for soil tillage applications. Its strong casing offers excellent durability and traction. The stubble-resistant tread compound features high cut-and-chip resistance.



	SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
			REC RIM	ALT RIM						
										
Ø24"	320/85 R 24 (12.4 R 24)	122 A8/B	W 11	W 10 W 9	329	1154	528	3449	550	STD
	380/85 R 24 (14.9 R 24)	131 A8/B	W 12	W 13 W 11	380	1256	566	3783	600	STD
Ø26"	420/85 R 26 (16.9 R 26)	138 A8/B	DW 15 L	W 14 L W 15 L W 16 L DW 16 L	450	1374	616	4115	650	STD
	460/85 R 26 (18.4 R 26)	143 A8/B	DW 15 L	W 15 L W 16 L DW 16 L	465	1442	642	4297	675	STD
Ø28"	320/85 R 28 (12.4 R 28)	124 A8/B	W 11	W 9 W 10	329	1255	577	3779	600	STD

STD: STANDARD

TECHNOLOGIES		PERFORMANCES	
			
			
A8/B	145 kg		

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference, SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
380/85 R 28 (14.9 R 28)	133 A8/B	W 12	W 11 W 13	390	1357	617	4127	650	STD
340/85 R 28 (13.6 R 28)	127 A8/B	W 12	W 11	353	1289	599	3908	625	STD
420/85 R 28 (16.9 R 28)	139 A8/B	W 15 L	W 14 L W 13	450	1425	640	4276	675	STD
Ø30"	420/85 R 30 (16.9 R 30)	W 15 L	W 14 L W 13	450	1476	656	4398	700	STD
	460/85 R 30 (18.4 R 30)	W 16 L	W 15 L W 14 L	475	1544	697	4648	725	STD

STD: STANDARD

TECHNOLOGIES		PERFORMANCES	
			
R1	A8/B		
	145 kg		
			
Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index			