

FLOTATION 648

| | |
|---------------------------|--|
| TIRE SIZE | 700/40 - 22.5 |
| UM | US STANDARD |
| CONSTRUCTION | BIAS |
| MACHINERY | HEUPRESSE / ERNTEMASCHINE / STREUMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 154 A8/150 B |
| LI/SS FREE ROLLING | 166 A8/ 162 B |



ABMESSUNGEN US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA-CODE | 94006489 | RC (IN) | 139.3 |
| SW (IN) | 27.6 | RIM REC | AG 24.00 |
| OD (IN) | 46.1 | ECE | E4-106R-002311 |
| SLR (IN) | 20.1 | PR | 16 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 26 | 29 | 32 |
|-----------|-------|-------|-------|
| 5 FR | 14550 | 15480 | 16360 |
| 10 FR | 13090 | 13930 | 14730 |
| 20 FR | 11640 | 12380 | 13080 |
| 25 FR | 10390 | 11060 | 11680 |
| 30 FR | 9360 | 9950 | 10470 |
| 5 DW | 10300 | 10950 | 11570 |
| 10 DW | 9260 | 9840 | 10420 |
| 20 DW | 8230 | 8750 | 9260 |
| 25 DW | 7350 | 7810 | 8270 |
| 30 DW | 6610 | 7030 | 7390 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.