

# AS 504

<b>TIRE SIZE</b>	<b>6.5/80 - 12</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	80 A8
<b>LI/SS FREE ROLLING</b>	93 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94038602	<b>RC (IN)</b>	72.3
<b>SW (IN)</b>	6.7	<b>RIM REC</b>	5 J
<b>OD (IN)</b>	23.9	<b>RIM ALT</b>	5 JA
<b>SLR (IN)</b>	11.1	<b>ECE</b>	E4-106R-002180

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	52
5 FR	2010
15 FR	1710
20 FR	1610
25 FR	1430
5 DW	1390
15 DW	1180
20 DW	1110
25 DW	990

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.