


# AS 504

<b>TIRE SIZE</b>	<b>16.5/85 - 24</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	SOLLEVATORE TELESOPICO / RIMORCHIO DA CAMPO / ATTREZZI AGRICOLI / SOLLEVATORE TELESOPICO
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	151 A8
<b>LI/SS FREE ROLLING</b>	163 A8



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94019090	<b>RC (IN)</b>	158.0
<b>SW (IN)</b>	16.3	<b>RIM REC</b>	W 13
<b>OD (IN)</b>	52.2	<b>RIM ALT</b>	W 14 L; W 15 L
<b>SLR (IN)</b>	23.0	<b>ECE</b>	E11-106R-003512

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	41
5 FR	15050
15 FR	12790
20 FR	12040
25 FR	10750
5 DW	10650
15 DW	9050
20 DW	8520
25 DW	7610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.