

PL 801

| | |
|---------------------|--|
| TIRE SIZE | 18X7 - 8 |
| UM | US STANDARD |
| CONSTRUCTION | ❖ BIAS |
| MACHINERY | ROTTERANDE HARV / SKÖRDEMASKIN / GAFFELTRUCK / SKÖRDEMASKIN / ARBETSFORDON / GAFFELTRUCK |
| VERSION | STANDARD |
| TIRE TYPE | TT |
| LI/SS | 121 A8 |



DIMENSIONER US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94006977 | RIM ALT | 5.00 F |
| SW (IN) | 6.8 | ECE | E11-106R-003642 |
| OD (IN) | 18.5 | PR | 16 |
| RIM REC | 4.33 R | | |

LOAD CAPACITY (LBS/TIRE)

| | |
|---------------------------|------------|
| MPH / PSI | 145 |
| 15 LOAD WHEEL | 4730 |
| 15 STEER WHEEL | 3635 |
| 5 OTHER VEHICLES | 4730 |
| 15 OTHER VEHICLES | 3635 |
| STATIC SIDE LOADER | 5490 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.