


# AGRIMAX V- FLECTO



|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>VF 710/55 R 34</b>  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | MOTORSTARK TRAKTOR / TRAKTOR   |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 170 D  |

## DIMENSIONER IS STANDARD

|                 |      |                |                  |
|-----------------|------|----------------|------------------|
| <b>SW (MM)</b>  | 708  | <b>RIM REC</b> | DW 25 B          |
| <b>OD (MM)</b>  | 1659 | <b>RIM ALT</b> | DW 27 B          |
| <b>SLR (MM)</b> | 726  | <b>ECE</b>     | E11-106R-0010831 |
| <b>RC (MM)</b>  | 4910 | <b>SRI</b>     | 775              |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR                            | 0.6  | 0.8  | 1    | 1.2  | 1.4  | 1.6  | 2    |
|---------------------------------------|------|------|------|------|------|------|------|
| 70                                    | 2675 | 3110 | 3600 | 4040 | 4475 | 4910 | 5460 |
| <b>FROM 65 TO 40</b>                  | 2940 | 3420 | 3960 | 4440 | 4920 | 5400 | 6000 |
| 30                                    | 2995 | 3485 | 4035 | 4525 | 5015 | 5505 | 6120 |
| 20                                    | 3055 | 3555 | 4115 | 4615 | 5115 | 5615 | 6240 |
| 10                                    | 3230 | 3760 | 4355 | 4880 | 5410 | 5940 | 6600 |
| <b>*UPTO 10 CYC WITH FRONT LOADER</b> | 4115 | 4785 | 5540 | 6215 | 6885 | 7560 | 8400 |
| 10HT                                  | 2995 | 3485 | 4035 | 4525 | 5015 | 5505 | 6120 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.