


# AGRIMAX FORCE



<b>TIRE SIZE</b>	<b>IF 710/60 R 34</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HARVESTER / HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	170 D

## DIMENSIONS US STANDARD

<b>USA CODE</b>	94022229	<b>RC (IN)</b>	201.8
<b>SW (IN)</b>	27.9	<b>RIM REC</b>	DW 25 B
<b>OD (IN)</b>	67.6	<b>ECE</b>	E4-106R-001485
<b>SLR (IN)</b>	30.0	<b>TRA CODE</b>	R1W

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	5530	6370	7340	8180	9140	9990	11190	12040
<b>FROM 40 TO 25</b>	6080	7010	8070	8990	10050	10980	12300	13200
20	6330	7290	8390	9350	10450	11410	12790	13760
12	6570	7560	8710	9710	10850	11850	13280	14290
5	7730	8900	10240	11420	12760	13930	15620	16800
<b>UPTO 20 CYC</b>	7900	9100	10480	11680	13060	14260	15980	17200
<b>UPTO 10 CYC</b>	9420	10860	12500	13930	15570	17010	19060	20500
<b>UPTO 5 CYC</b>	10340	11920	13710	15290	17080	18660	20910	22490
5 HT	6330	7290	8390	9350	10450	11410	12790	13760

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.