

# XL GRIP (G3)

|                     |                   |
|---------------------|-------------------|
| <b>TIRE SIZE</b>    | <b>13.00 - 24</b> |
| <b>UM</b>           | US STANDARD       |
| <b>CONSTRUCTION</b> | ⊠ BIAS            |
| <b>MACHINERY</b>    | GRADER            |
| <b>VERSION</b>      | STANDARD          |
| <b>TL/TT</b>        | TL                |



## DIMENSIONS US STANDARD

|                 |          |                 |                              |
|-----------------|----------|-----------------|------------------------------|
| <b>USA CODE</b> | 94047796 | <b>RIM RE</b>   |                              |
| <b>OD (IN)</b>  | 51.0     | <b>RIM ALT</b>  | 9.00/1.5 (DC) ; 10.00/VA SDC |
| <b>SLR (IN)</b> | 23.7     | <b>PR</b>       | 16                           |
| <b>RC (IN)</b>  | 152.4    | <b>TRA CODE</b> | G3                           |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>58</b> |
| 25               | 7140      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.