

# EARTHMAX SR 49 M



**EARTHMAX**  
RADIAL OTR TIRES

# EARTHMAX SR 49 M



EARTHMAX SR 49 M is an All Steel radial tire with a special non-directional pattern designed for load haul dumps (LHD), low profile dump trucks (LPDT), loaders and dozers operating in severe rocky conditions primarily in underground mining. EARTHMAX SR 49 M is ideal for severe operations requiring exceptional traction and stability.



|      | SIZE      | TT/TL | TRA CODE | STAR RATING | LI/SS           | RIM                                                                               |                                                                                   | TKPH | O.W.<br>(mm) | OD<br>(mm) | SLR<br>(mm) | RC<br>(mm) | THREAD DEPTH | VERSION |
|------|-----------|-------|----------|-------------|-----------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------|--------------|------------|-------------|------------|--------------|---------|
|      |           |       |          |             |                 | REC RIM                                                                           | ALT RIM                                                                           |      |              |            |             |            |              |         |
|      |           |       |          |             |                 |  |  |      |              |            |             |            |              |         |
| Ø25" | 26.5 R 25 | TL    | SH4      | ****        | -               | 22.00/3.0                                                                         | -                                                                                 | 0    | 708          | 1782       | 801         | 5297       | 56           | CR      |
|      | 29.5 R 25 | TL    | E4/L4    | **          | 200 B<br>216 A2 | 25.00/3.5                                                                         | -                                                                                 | 220  | 780          | 1905       | 844         | 5600       | 57           | CR      |
|      | 29.5 R 25 | TL    | E4/L4    | ****/***    | -               | 25.00/3.5                                                                         | -                                                                                 | 0    | 780          | 1905       | 844         | 5600       | 57           | CR      |
|      | 29.5 R 25 | TL    | L4       | **          | 216 A2          | 25.00/3.5                                                                         | -                                                                                 | 0    | 780          | 1905       | 844         | 5600       | 57           | CR      |
|      | 26.5 R 25 | TL    | E4/L4    | **/*        | 193 B<br>202 A2 | 22.00/3.0                                                                         | -                                                                                 | 165  | 708          | 1782       | 801         | 5297       | 56           | CR      |

CR: CUT RESISTANT COMPOUND

| TECHNOLOGIES                                                                        |                                                                                     | PERFORMANCES                                                                        |                                                                                     |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |  |  |  |
|  |  |  |  |
| B                                                                                   | 223 kg                                                                              |                                                                                     |                                                                                     |

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

| SIZE      | TT/TL | TRA CODE | STAR RATING | LI/SS           | RIM                                                                               |                        | TKPH | O.W.<br>(mm) | OD<br>(mm) | SLR<br>(mm) | RC<br>(mm) | THREAD DEPTH | VERSION |
|-----------|-------|----------|-------------|-----------------|-----------------------------------------------------------------------------------|------------------------|------|--------------|------------|-------------|------------|--------------|---------|
|           |       |          |             |                 | REC RIM                                                                           | ALT RIM                |      |              |            |             |            |              |         |
|           |       |          |             |                 |  |                        |      |              |            |             |            |              |         |
| 29.5 R 25 | TL    | E4/L4    | **/*        | 200 B<br>208 A2 | 25.00/3.5                                                                         | -                      | 220  | 780          | 1905       | 844         | 5600       | 57           | CR      |
| 29.5 R 25 | TL    | SH4      | ****        | -               | 25.00/3.5                                                                         | -                      | 0    | 780          | 1905       | 844         | 5600       | 57           | CR      |
| 26.5 R 25 | TL    | E4/L4    | ****/**     | -               | 22.00/3.0                                                                         | -                      | 0    | 708          | 1782       | 801         | 5297       | 56           | CR      |
| 29.5 R 25 | TL    | L4       | *           | 208 A2          | 25.00/3.5                                                                         | -                      | 0    | 780          | 1905       | 844         | 5600       | 57           | CR      |
| 26.5 R 25 | TL    | L4       | *           | 202 A2          | 22.00/3.0                                                                         | -                      | 0    | 708          | 1782       | 801         | 5297       | 56           | CR      |
| 26.5 R 25 | TL    | L4       | **          | 209 A2          | 22.00/3.0                                                                         | -                      | 0    | 708          | 1782       | 801         | 5297       | 56           | CR      |
|           |       |          |             |                 |                                                                                   |                        |      |              |            |             |            |              |         |
| 29.5 R 29 | TL    | SH4      | ****        | -               | 25.00/3.5                                                                         | 24.00/3.5<br>26.00/3.5 | 0    | 786          | 2006       | 906         | 6320       | 60           | CR      |
| 29.5 R 29 | TL    | L4       | ***         | 223 A2          | 25.00/3.5                                                                         | 24.00/3.5<br>26.00/3.5 | 0    | 786          | 2006       | 906         | 6320       | 60           | CR      |

CR: CUT RESISTANT COMPOUND

| TECHNOLOGIES                                                                        |                                                                                     | PERFORMANCES                                                                                                                                                                     |                                                                                     |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |  |                                                                                               |  |
|  |  |                                                                                               |  |
| E4/L4/SH4                                                                           |                                                                                     | Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index |                                                                                     |
| B                                                                                   |                                                                                     | 223 kg                                                                                                                                                                           |                                                                                     |