


# AGRIMAX RT 855

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>420/80 R 46</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRACTOR / IMPLEMENTS   |
| <b>VERSION</b>      | STANDARD   |
| <b>TL/TT</b>        | TL   |
| <b>LI/SS</b>        | 151 D ; 162 A2   |



## DIMENSIONS US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94046089 | <b>RC (IN)</b> | 222.1          |
| <b>SW (IN)</b>  | 16.5     | <b>RIM REC</b> | W 13           |
| <b>OD (IN)</b>  | 72.4     | <b>RIM ALT</b> | W 12           |
| <b>SLR (IN)</b> | 34.0     | <b>ECE</b>     | E4-106R-001730 |

## LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 9    | 12   | 15   | 17   | 20   | 23   | 29   | 35    |
|-----------|------|------|------|------|------|------|------|-------|
| 40        | 3580 | 4110 | 4720 | 5320 | 5940 | 6550 | 7080 | 7610  |
| 30        | 3760 | 4320 | 4960 | 5600 | 6240 | 6880 | 7440 | 7990  |
| 25        | 3920 | 4510 | 5170 | 5840 | 6500 | 7180 | 7760 | 8330  |
| 20        | 4120 | 4730 | 5430 | 6130 | 6830 | 7530 | 8150 | 8750  |
| 5         | 4930 | 5650 | 6490 | 7330 | 8170 | 9010 | 9740 | 10470 |
| 5 LT      | 4790 | 5510 | 6330 | 7140 | 7960 | 8770 | 9490 | 10200 |
| 5 HT      | 4120 | 4730 | 5430 | 6130 | 6830 | 7530 | 8150 | 8750  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.