

AGRIMAX V-FLECTO

TYRE SIZE	VF 710/70 R 42
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	STANDARD
TL/TT	TL
LI/SS	185 D



DIMENSIONS IS STANDARD

SW (MM)	715	RIM REC	DW 25 B
OD (MM)	2061	RIM ALT	DW 23 B; DW 24 B
SLR (MM)	921	ECE	E11-106R-0010959
RC (MM)	6182	SRI	975

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	3960	4545	5220	5895	6565	7240	7915	8415
FROM 65 TO 40	4350	4995	5735	6475	7215	7955	8695	9250
30	4435	5095	5850	6605	7360	8115	8870	9435
20	4525	5195	5965	6735	7505	8275	9045	9620
10	4785	5495	6310	8125	7940	8755	9565	10175
*UPTO 10 CYC WITH FRONT LOADER	6090	6995	8030	9065	10105	11140	12175	12950
10 HT	4435	5095	5850	6605	7360	8115	8870	9435

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.