

FLOTATION 648

TIRE SIZE	500/50 - 22.5
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	HEUPRESSE / ERNTEMASCHINE / STREUMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	151 A8/147 B
LI/SS FREE ROLLING	163 A8/159 B



ABMESSUNGEN US STANDARD

USA-CODE	94037827	RC (IN)	126.0
SW (IN)	19.7	RIM REC	AG 16.00
OD (IN)	42.1	ECE	E11-106R-003400
SLR (IN)	18.7	PR	20

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	49	52	55
5 FR	14110	14580	15050
10 FR	12700	13130	13550
20 FR	11290	11660	12040
25 FR	10070	10420	10750
30 FR	9070	9380	9640
5 DW	9990	10330	10650
10 DW	8980	9290	9580
20 DW	7990	8260	8520
25 DW	7130	7370	7610
30 DW	6420	6640	6780

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.