


# AGRIMAX TERIS

<b>TIRE SIZE</b>	<b>IF 710/75 R 34</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	COSECHADORA / COSECHADORA DE ALGODÓN
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	184 A8/B



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94058723	<b>RC (IN)</b>	230.4
<b>SW (IN)</b>	28.2	<b>RIM REC</b>	DW 25 B
<b>OD (IN)</b>	76.0	<b>ECE</b>	E11-106R-004899
<b>SLR (IN)</b>	34.3		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46
30	7740	8930	10120	11510	12700	14090	15670	16860	18450	19840
25	7740	8930	10120	11510	12700	14090	15670	16860	18450	19840
20	8290	9560	10840	12320	13590	15080	16780	18050	19750	21230
10 CYC*	12780	14740	16700	18990	20950	23250	25870	27830	30460	32740
5 CYC*	13930	16070	18220	20720	22860	25360	28220	30360	33220	35710

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.