


AW 711

| | |
|---------------------|--|
| TIRE SIZE | 380/70 R 19.5 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | SKÖRDEMASKIN / ARBETSFORDON / SKÖRDEMASKIN / ARBETSFORDON |
| VERSION | STUBBLE RESISTANT |
| TIRE TYPE | TL |
| LI/SS | 159 A8/B |



DIMENSIONER IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 389 | RIM REC | 11.75 |
| OD (MM) | 1019 | RIM ALT | 12.75 |
| SLR (MM) | 444 | ECE | E11-106R-006808 |
| RC (MM) | 3038 | SRI | 475 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.2 | 1.6 | 2 | 2.4 | 2.8 | 3.2 | 3.6 | 4 | 5 | 5.5 |
|------------|------|------|------|------|------|------|------|------|------|------|------|
| 50 | 1295 | 1665 | 2035 | 2345 | 2715 | 3085 | 3305 | 3655 | 4005 | 4115 | 4375 |
| 40 | 1295 | 1665 | 2035 | 2345 | 2715 | 3085 | 3305 | 3655 | 4005 | 4115 | 4375 |
| 30 | 1450 | 1865 | 2280 | 2625 | 3040 | 3455 | 3700 | 4095 | 4485 | 4610 | 4900 |
| 25 | 1540 | 1980 | 2425 | 2790 | 3235 | 3675 | 3935 | 4355 | 4770 | 4900 | 5210 |
| 20 | 1630 | 2100 | 2565 | 2955 | 3420 | 3890 | 4165 | 4610 | 5050 | 5185 | 5515 |
| 10 | 1810 | 2330 | 2850 | 3280 | 3800 | 4320 | 4625 | 5115 | 5605 | 5760 | 6125 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.