DATA SHEET

PRINTED ON
23-04-2026

AGRIMAX SIRIO

TYRE SIZE	**540/65 R 38**
UM	IS STANDARD
CONSTRUCTION	RADIAL
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	HIGH SPEED
TYRE TYPE	TL
LI/SS	153 D ; 150 E

DIMENSIONS IS STANDARD

SW (MM)	530	**RIM REC**	W 16 L
OD (MM)	1667	**RIM ALT**	W 18 L
SLR (MM)	769	**ECE**	E4-106R-000816
RC (MM)	5050	**SRI**	800

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	1575	1810	2080	2345	2615	2885	3120	3350
65	1720	1975	2265	2555	2850	3140	3395	3650
50	1805	2075	2380	2685	2995	3300	3570	3835
40	1880	2160	2480	2800	3120	3440	3720	4000
25	2040	2340	2685	3035	3380	3725	4030	4330
10	2575	2960	3395	3835	4275	4710	5095	5475

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..