


# AGRIMAX RT 945

<b>TIRE SIZE</b>	<b>380/90 R 50</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	FELDSPRITZE / TRACTOR / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	151 A8/B



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94037025	<b>RC (IN)</b>	232.3
<b>SW (IN)</b>	15.0	<b>RIM REC</b>	W 12
<b>OD (IN)</b>	76.9	<b>RIM ALT</b>	W 11 ; W 13
<b>SLR (IN)</b>	35.7	<b>ECE</b>	E4-106R-001487

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41
30	4110	5320	6550	7080	7600	-
25	4110	5320	6550	7080	7600	-
20	4410	5710	7010	7580	8150	-
5	6050	7420	9020	10500	11070	11410

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.