

AGRIMAX TURF RT 333

| | |
|---------------------|---|
| TIRE SIZE | 480/70 R 28 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / МАШИНА ДЛЯ СБОРА ФРУКТОВ / МИНИ- ТРАКТОР / ТРАКТОР-ТЯГАЧ / КОМБАЙН |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 140 A8 ; 140 B |



РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 479 | RIM REC | W 15 L |
| OD (MM) | 1421 | RIM ALT | W 14 L; W 16 L |
| SLR (MM) | 631 | ECE | E11-106R-009049 |
| RC (MM) | 4228 | SRI | 675 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 50 | 1375 | 1600 | 1825 | 2050 | 2275 | 2500 |
| 40 | 1375 | 1600 | 1825 | 2050 | 2275 | 2500 |
| 30 | 1475 | 1715 | 1955 | 2195 | 2435 | 2675 |
| 10 LT | 1845 | 2145 | 2450 | 2750 | 3050 | 3350 |
| 10 HT | 1475 | 1715 | 1955 | 2195 | 2435 | 2675 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.