


# MULTIMAX MP 525

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>405/70 R 18</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL                             |
| <b>MACHINERY</b>    | VEICULO UNIVERSAL / LEVANTADOR<br>TELESCÓPICO / CARREGADORA<br>COMPACTA / LEVANTADOR<br>TELESCÓPICO / MOTONIVELADORA |
| <b>VERSÃO</b>       | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 146 J ; 141 B ; 153 A2   |



## DIMENSÕES US STANDARD

|                   |          |                |                 |
|-------------------|----------|----------------|-----------------|
| <b>CÓDIGO USA</b> | 94075539 | <b>RIM REC</b> | 13              |
| <b>OD (IN)</b>    | 40.4     | <b>RIM ALT</b> | 11; 12          |
| <b>SLR (IN)</b>   | 18.2     | <b>ECE</b>     | E11-54R-0022030 |
| <b>RC (IN)</b>    | 122.9    |                |                 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 54   | 58   |
|-----------|------|------|
| 62        | 6150 | 6600 |
| 30        | 5680 | -    |
| 5         | 8050 | -    |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.