

RIDEMAX FROST

TIRE SIZE	480/80 R 38 IND
UM	IS STANDARD
CONSTRUCTION	
MACHINERY	TRACTOR
VERSION	STEEL BELTED
TL/TT	TL
LI/SS	166 A8 ; 161 D



DIMENSIONS IS STANDARD

SW (MM)	470	RIM REC	DW 15 L
OD (MM)	1733	RIM ALT	DW 16 L
SLR (MM)	797	ECE	E11-106R-0011849
RC (MM)	5294	SRI	825

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2	2.4	2.6	2.8	3	3.2
65	2130	2730	3330	3655	3935	4120	4305	4490	4625
50	2300	2950	3600	3950	4250	4450	4650	4850	4995
40	2440	3130	3820	4190	4505	4720	4930	5145	5300
30	2555	3275	4000	4385	4720	4940	5165	5385	5550
20	2685	3440	4200	4610	4960	5190	5425	5660	5830
10	3065	3930	4800	5265	5665	5930	6195	6465	6660
5	3555	4560	5565	6105	6570	6880	7185	7495	7725

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.