

# FLOTATION TR 675

<b>TIRE SIZE</b>	<b>550/60 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	ARBETSFORDON / SLÄPVAGN / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	154 A8/150 B
<b>LI/SS FREE ROLLING</b>	167 A8/163 B



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94019816	<b>RC (IN)</b>	143.3
<b>SW (IN)</b>	21.7	<b>RIM REC</b>	AG 16.00
<b>OD (IN)</b>	49.6	<b>ECE</b>	E11-106R-004397
<b>SLR (IN)</b>	21.5	<b>PR</b>	16

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	35	38	41
<b>5 FR</b>	15370	16110	16820
<b>10 FR</b>	13830	14490	15130
<b>20 FR</b>	12300	12890	13460
<b>25 FR</b>	10980	11510	12010
<b>30 FR</b>	9880	10360	10750
<b>5 DW</b>	10570	11080	11570
<b>10 DW</b>	9510	9980	10420
<b>20 DW</b>	8450	8860	9260
<b>25 DW</b>	7550	7910	8270
<b>30 DW</b>	6800	7120	7390

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.