


AGRIMAX V- FLECTO



TIRE SIZE	VF 710/75 R 42
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	184 D

DIMENSIONS US STANDARD

USA CODE	94075447	RC (IN)	252.4
SW (IN)	28.7	RIM REC	DW 24 B
OD (IN)	84.6	RIM ALT	DW 23 B; DW 25 B
SLR (IN)	36.9	ECE	E11-106R-009074

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	9030	10470	11920	13540	14980	16420	18050
FROM 40 TO 25	9920	11510	13090	14880	16470	18050	19840
20	10120	11730	13350	15180	16790	18410	20240
12	10320	11960	13610	15480	17120	18770	20630
5	10910	12650	14400	16370	18110	19850	21820
*UPTO 5 CYC WITH FRONT LOADER	13890	16100	18330	20830	23050	25270	27780
5 HT	10120	11730	13350	15180	16790	18410	20240

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.