

# AGRIMAX FORCE

|                  |                                                          |
|------------------|----------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>IF 750/75 R 46 CFO</b>                                |
| <b>UM</b>        | IS STANDARD                                              |
| <b>MACHINERY</b> | MOISSONNEUSE / TRACTEUR DE<br>FORTE PUISSANCE / TRACTEUR |
| <b>VERSION</b>   | STANDARD                                                 |
| <b>TIRE TYPE</b> | TL                                                       |
| <b>LI/SS</b>     | 186 D                                                    |



## DIMENSIONS IS STANDARD

|                 |      |                 |                 |
|-----------------|------|-----------------|-----------------|
| <b>SW (MM)</b>  | 742  | <b>RIM REC</b>  | DW 25 B         |
| <b>OD (MM)</b>  | 2294 | <b>ECE</b>      | E11-106R-006491 |
| <b>SLR (MM)</b> | 1032 | <b>SRI</b>      | 1075            |
| <b>RC (MM)</b>  | 6802 | <b>TRA CODE</b> | R1W             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR           | 0.6  | 0.8  | 1.0   | 1.2   | 1.4   | 1.6   | 2.0   | 2.4   |
|----------------------|------|------|-------|-------|-------|-------|-------|-------|
| <b>70</b>            | 4060 | 4665 | 5355  | 6050  | 6740  | 7430  | 8125  | 8645  |
| <b>FROM 65 TO 40</b> | 4465 | 5130 | 5890  | 6650  | 7410  | 8170  | 8930  | 9500  |
| <b>30</b>            | 4640 | 5335 | 6125  | 6915  | 7705  | 8495  | 9285  | 9880  |
| <b>20</b>            | 4820 | 5540 | 6360  | 7180  | 8000  | 8820  | 9640  | 10260 |
| <b>10</b>            | 5670 | 6515 | 7480  | 8445  | 9410  | 10370 | 11340 | 12065 |
| <b>UPTO 30 CYC</b>   | 5800 | 6665 | 7655  | 8645  | 9630  | 10620 | 11605 | 12350 |
| <b>UPTO 15 CYC</b>   | 6920 | 7950 | 9125  | 10305 | 11485 | 12660 | 13840 | 14725 |
| <b>UPTO 10 CYC</b>   | 7590 | 8720 | 10010 | 11305 | 12595 | 13885 | 15180 | 16150 |
| <b>10HT</b>          | 4640 | 5335 | 6125  | 6915  | 7705  | 8495  | 9285  | 9880  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.