


AGRIMAX RT 855

TIRE SIZE	480/80 R 50
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	FELDSPRITZE / TRAUBENERNTEMASCHINE / TRACTOR / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	176 A8



ABMESSUNGEN IS STANDARD

SW (MM)	489	RIM REC	DW 16 L
OD (MM)	2036	RIM ALT	DW 15 L; W 15 L
SLR (MM)	945	ECE	E4-106R-001495
RC (MM)	6183	SRI	975

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4	5.0
50	2060	2365	2715	3065	3415	3765	4070	4375	4760	5185	5470	5825	6320	7100
40	2060	2365	2715	3065	3415	3765	4070	4375	4760	5185	5470	5825	6320	7100
30	2205	2530	2905	3280	3655	4030	4360	4685	5095	5550	5855	6235	6765	7600
10 LT	2760	3170	3640	4110	4575	5045	5455	5865	6380	6950	7330	7805	8470	9515
10 HT	2205	2530	2905	3280	3655	4030	4360	4685	5095	5550	5855	6235	6765	7600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.