

# RIB 774 (A)

<b>TIRE SIZE</b>	10.5/65 - 16
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / КОМБАЙН / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	INDUSTRIAL
<b>TIRE TYPE</b>	TT
<b>LI/SS FREE ROLLING</b>	130 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94076130	<b>RC (IN)</b>	85.9
<b>SW (IN)</b>	10.4	<b>RIM REC</b>	W 9
<b>OD (IN)</b>	29.3	<b>RIM ALT</b>	W 8 L
<b>SLR (IN)</b>	13.3	<b>PR</b>	14

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	77
5 FR	5860
15 FR	4980
20 FR	4700
25 FR	4190

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.