

# TR 117

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>14.9 - 24</b>                         |
| <b>UM</b>           | IS STANDARD                              |
| <b>CONSTRUCTION</b> | ⊠ BIAS                                   |
| <b>MACHINERY</b>    | ARROSEUR À PIVOT / OUTILLAGE<br>AGRICOLE |
| <b>VERSION</b>      | STANDARD                                 |
| <b>TIRE TYPE</b>    | TT                                       |
| <b>LI/SS</b>        | 123 A6                                   |



## DIMENSIONS IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 378  | <b>RIM REC</b> | W 13           |
| <b>OD (MM)</b>  | 1245 | <b>RIM ALT</b> | W 11; W 12     |
| <b>SLR (MM)</b> | 575  | <b>ECE</b>     | E4-106R-002027 |
| <b>RC (MM)</b>  | 3660 | <b>PR</b>      | 6              |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.40 | 1.80 |
|------------|------|------|
| 30         | 1550 | ---  |
| CREEP      | ---  | 2870 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.