


AS 504

| | |
|---------------------------|--|
| TIRE SIZE | 7.00 - 12 |
| UM | IS STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | TELESKOPLASTARE / ÅKERSLÄP / ARBETSFORDON / TELESKOPLASTARE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 83 A8 |
| LI/SS FREE ROLLING | 95 A8 |



DIMENSIONER IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 187 | RIM REC | 4.5 |
| OD (MM) | 683 | ECE | E4-106R-001956 |
| SLR (MM) | 311 | PR | 6 |
| RC (MM) | 2049 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 2.50 |
|------------|------|
| 10 FR | 965 |
| 25 FR | 820 |
| 30 FR | 775 |
| 40 FR | 690 |
| 10 DW | 680 |
| 25 DW | 575 |
| 30 DW | 545 |
| 40 DW | 485 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.