

FLOTATION 648

TIRE SIZE	650/65 - 30.5
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	HEUPRESSE / ERNTEMASCHINE / STREUMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	HD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	169 A8/165 B
LI/SS FREE ROLLING	181 A8/178 B



ABMESSUNGEN IS STANDARD

SW (MM)	670	RIM REC	AG 20.00
OD (MM)	1660	ECE	E11-106R-004563
SLR (MM)	710	PR	18
RC (MM)	4935		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.30	2.40	2.50
10 FR	10995	11275	11550
20 FR	9895	10150	10395
30 FR	8800	9020	9240
40 FR	7855	8055	8250
50 FR	7070	7250	7500
10 DW	7735	7930	8120
20 DW	6960	7140	7310
30 DW	6190	6345	6495
40 DW	5525	5665	5800
50 DW	4975	5100	5150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.