


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>420/85 R 24</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS
<b>VERSION</b>	SPECIAL
<b>TL/TT</b>	TL
<b>LI/SS</b>	137 A8/B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94047482	<b>RC (IN)</b>	153.5
<b>SW (IN)</b>	17.7	<b>RIM REC</b>	W 15 L
<b>OD (IN)</b>	52.1	<b>RIM ALT</b>	W 14 L ; W 13
<b>SLR (IN)</b>	22.9	<b>ECE</b>	E4-106R-000595

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	2790	3250	3700	4170	4620	5070
25	2790	3250	3700	4170	4620	5070
20	3000	3480	3970	4460	4950	5430
5 LT	3750	4350	4970	5580	6190	6800
5 HT	3000	3480	3970	4460	4950	5430

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.