


AGRIMAX RT 765

| | |
|---------------------|--|
| TYRE SIZE | 200/70 R 16 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR / IMPLEMENTS |
| VERSION | STANDARD |
| TYRE TYPE | TL |
| LI/SS | 94 A8/B |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94026869 | RC (IN) | 81.1 |
| SW (IN) | 7.8 | RIM REC | W 6 |
| OD (IN) | 27.0 | RIM ALT | W 7 |
| SLR (IN) | 12.4 | ECE | E4-106R-000607 |

LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|-----------|-----|------|------|------|------|------|------|------|
| 30 | 690 | 800 | 930 | 1040 | 1160 | 1280 | 1380 | 1480 |
| 25 | 690 | 800 | 930 | 1040 | 1160 | 1280 | 1380 | 1480 |
| 20 | 750 | 860 | 990 | 1110 | 1250 | 1370 | 1480 | 1590 |
| 5 LT | 940 | 1080 | 1230 | 1390 | 1550 | 1710 | 1850 | 1980 |
| 5 HT | 750 | 860 | 990 | 1110 | 1250 | 1370 | 1480 | 1590 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.