


# AGRIMAX V- FLECTO



<b>TIRE SIZE</b>	<b>VF 540/65 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	162 D

## DIMENSIONS US STANDARD

<b>USA CODE</b>	94059119	<b>RC (IN)</b>	196.1
<b>SW (IN)</b>	21.6	<b>RIM REC</b>	DW 20 B
<b>OD (IN)</b>	66.0	<b>RIM ALT</b>	DW 18 L
<b>SLR (IN)</b>	29.9	<b>ECE</b>	E11-106R-005020

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	4850	5610	6370	7240	7900	8580	9520
<b>FROM 40 TO 25</b>	5330	6170	7010	7960	8690	9420	10470
20	5430	6290	7140	8110	8850	9610	10680
12	5540	6420	7290	8270	9030	9800	10890
5	5860	6790	7700	8750	9550	10360	11520
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	7460	8640	9810	11130	12160	13190	14660
5 HT	5430	6290	7140	8110	8850	9610	10680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.