

TR 135



TR 135



TR 135 is best suitable for tractors in soil tillage applications. Its reinforced casing and the special cut-and-chip resistance compound provide an extended tire life-cycle. Traction, self-cleaning proprieties and load capacity are key features which make the TR 135 tire the ideal partner even on the most difficult ground conditions.



	SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
			REC RIM	ALT RIM						
										
Ø16"	12.4 - 16	97 A6	W 11	W 9 9 W 10	326	960	431	2852	-	STD
	12.4 - 16	111 A6	W 11	W 9 9 W 10	326	960	431	2852	-	STD
Ø20"	9.5 - 20	107 A6	W 8	W 7	240	955	454	2888	-	HD
	8.00 - 20	111 A6	5.50 F	-	225	965	448	2837	-	STD
	12.4 - 20	116 A6	W 11	W 9 9 W 10 11	325	1075	500	3160	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
			

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
11.2 - 20	111 A6	W 10	W 9 9	292	1020	466	3077	-	STD
10.00 - 20	152 A2	7.5	-	280	1075	495	3160	-	STD
9.5 - 20	107 A6	W 8	W 7	240	955	454	2888	-	STD
8.00 - 20	105 A6	5.50 F	-	225	965	448	2837	-	STD
9.5 - 20	102 A6	W 8	W 7	240	955	444	2881	-	STD
12.4 - 20	116 A6	W 11	W 9 9 W 10 11	325	1075	500	3160	-	HD
Ø24"	12.4 - 24	128 A6	W 11 W 9 W 10	315	1160	543	3573	550	STD
	13.6 - 24	123 A6	W 12 W 11	355	1220	562	3698	-	STD
	8.3 - 24	100 A6	W 7 W 6	211	995	469	2985	-	STD
	13.6 - 24	123 A6	W 12 W 11	355	1220	562	3698	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
12.4 - 24	121 A6	W 11	W 9 W 10	315	1160	531	3477	550	HD
11.2 - 24	116 A6	W 10	W 9	284	1105	507	3303	525	HD
14.9 - 24	135 A6	W 13	W 12 W 11	378	1265	576	3837	600	STD
12.4 - 24	125 A6	W 11	W 9 W 10	315	1160	543	3573	550	STD
8.3 - 24	105 A6	W 7	W 6	211	995	469	2985	-	HD
11.2 - 24	120 A6	W 10	W 9	284	1105	517	3399	525	HD
13.6 - 24	130 A6	W 12	W 11	355	1220	562	3698	-	HD
16.9 - 24	136 A6	W 15 L	W 14 L	429	1335	613	3925	-	STD
14.9 - 24	135 A6	W 13	W 12 W 11	378	1265	576	3837	600	STD
12.4 - 24	121 A6	W 11	W 9 W 10	315	1160	543	3573	550	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
 R1	 A6	 	  
		 	

Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
14.9 - 24	132 A6	W 13	W 11 W 12	378	1265	576	3837	600	HD
11.2 - 24	110 A6	W 10	W 9	284	1105	517	3399	525	STD
16.9 - 24	140 A6	W 15 L	W 14 L	429	1335	601	4075	-	HD
11.2 - 24	120 A6	W 10	W 9	284	1105	517	3399	525	HD
9.5 - 24	116 A6	W 8	W 7	241	1060	502	3234	-	STD
14.9 - 24	128 A6	W 13	W 12 W 11	378	1265	576	3837	600	STD
14.9 - 24	128 A6	W 13	W 12 W 11	378	1265	570	3769	600	HD
8.3 - 24	105 A6	W 7	W 6	211	995	475	3076	-	STD
16.9 - 24	133 A6	W 15 L	W 14 L	429	1335	613	3925	-	HD
14.9 - 24	135 A6	W 13	W 12 W 11	378	1265	576	3837	600	HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
11.2 - 24	116 A6	W 10	W 9	284	1105	517	3399	25	STD
12.4 - 24	128 A6	W 11	W 9 W 10	315	1160	543	3573	550	SPL
14.9 - 24	128 A6	W 13	W 12 W 11	378	1265	576	3837	600	STD
14.9 - 24	128 A6	W 13	W 11 W 12	378	1265	570	3769	600	HD
11.2 - 24	116 A6	W 10	W 9	284	1105	517	3399	525	STD
13.6 - 24	123 A6	W 12	W 11	355	1220	562	3698	-	HD
12.4 - 24	121 A6	W 11	W 9 W 10	315	1160	543	3523	550	STD
16.9 - 24	133 A6	W 15 L	W 14 L	429	1335	613	3925	-	STD
9.5 - 24	116 A6	W 8	W 7	241	1060	502	3234	-	HD
13.6 - 24	130 A6	W 12	W 11	355	1220	562	3698	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
16.9 - 24	136 A6	W 15 L	W 14 L	429	1335	613	3925	-	STD
9.5 - 24	112 A6	W 8	W 7	241	1060	502	3234	-	HD
9.5 - 24	112 A6	W 8	W 7	241	1060	502	3234	-	STD
8.3 - 24	111 A6	W 7	W 6	211	995	469	2985	-	HD
16.9 - 24	133 A6	W 15 L	W 14 L	429	1335	613	3925	-	STD
12.4 - 24	115 A6	W 11	W 9 W 10	315	1160	543	3573	550	STD
12.4 - 24	121 A6	W 11	W 9 W 10	315	1160	531	3477	550	HD
9.5 - 24	106 A6	W 8	W 7	241	1060	502	3234	-	STD
12.4 - 24	128 A6	W 11	W 9 W 10	315	1160	543	3573	550	STD
Ø26"	14.9 - 26	129 A6	W 13 W 11 W 12	375	1315	599	3947	-	HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
23.1 - 26	153 A6	DW 20 B DW 20 A	-	587	1585	700	4615	750	STD
23.1 - 26	161 A6	DW 20 B DW 20 A	-	587	1585	700	4615	750	DB
23.1 - 26	159 A6	DW 20 B DW 20 A	-	587	1585	700	4615	750	DB
23.1 - 26	153 A6	DW 20 B DW 20 A	-	587	1585	700	4615	750	STD
16.9 - 26	137 A6	W 15 L	W 14 L	430	1380	625	4183	-	STD
23.1 - 26	153 A6	DW 20 B DW 20 A	-	587	1585	700	4615	750	DB
16.9 - 26	140 A6	W 15 L	W 14 L	430	1380	625	4183	-	STD
23.1 - 26	159 A6	DW 20 B DW 20 A	-	587	1585	700	4615	750	STD
16.9 - 26	137 A6	W 15 L	W 14 L	430	1380	625	4183	-	STD
23.1 - 26	159 A6	DW 20 B DW 20 A	-	587	1585	700	4615	750	HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
			

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
23.1 - 26	159 A6	DW 20 B DW 20 A	-	587	1585	700	4615	750	STD
14.9 - 26	136 A6	W 13	W 11 W 12	375	1315	599	3947	-	STD
23.1 - 26	156 A6	DW 20 B DW 20 A	-	587	1585	700	4615	750	STD
14.9 - 26	129 A6	W 13	W 11 W 12	375	1315	599	3947	-	STD
23.1 - 26	159 A6	DW 20 B DW 20 A	-	587	1585	700	4615	750	DB HD
23.1 - 26	153 A6	DW 20 B DW 20 A	-	587	1585	700	4615	750	DB
Ø28"	14.9 - 28	125 A6	W 13 W 11 W 12	378	1365	634	4170	650	STD
	11.2 - 28	118 A6	W 10 W 9	284	1205	565	3543	575	STD
	9.5 - 28	108 A6	W 8 W 7	235	1155	548	3557	-	STD
	13.6 - 28	134 A6	W 12 W 11	345	1310	606	3908	625	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
8.3 - 28	108 A6	W 7	W 6	213	1104	519	3347	-	STD
14.9 - 28	137 A6	W 13	W 11 W 12	378	1365	634	4170	650	STD
18.4 - 28	147 A6	W 16 L	W 15 L	467	1501	691	4413	-	STD
14.9 - 28	139 A6	W 13	W 11 W 12	378	1365	634	4170	650	STD
12.4 - 28	131 A6	W 11	W 9 W 10	325	1260	584	3876	600	STD
14.9 - 28 (28)	130 A6	W 13	W 11 W 12	378	1365	634	4170	650	STD
12.4 - 28	123 A6	W 11	W 9 W 10	325	1260	584	3876	600	HD
14.9 - 28	137 A6	W 13	W 11 W 12	378	1365	634	4170	650	HD
11.2 - 28	122 A6	W 10	W 9	284	1205	565	3543	575	STD
9.5 - 28	114 A6	W 8	W 7	235	1155	548	3557	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
13.6 - 28	137 A6	W 12	W 11	345	1310	606	3908	625	STD
14.9 - 28	130 A6	W 13	W 11 W 12	378	1365	634	4170	650	HD
8.3 - 28	103 A6	W 7	W 6	213	1104	519	3347	-	STD
14.9 - 28	130 A6	W 13	W 11 W 12	378	1365	634	4170	650	STD
13.6 - 28	125 A6	W 12	W 11	345	1310	606	3908	625	STD
13.6 - 28	125 A6	W 12	W 11	345	1310	607	4023	625	HD
12.4 - 28	123 A6	W 11	W 9 W 10	325	1260	584	3876	600	STD
12.4 - 28	117 A6	W 11	W 9 W 10	325	1260	584	3876	600	STD
12.4 - 28	127 A6	W 11	W 9 W 10	325	1260	584	3876	600	STD
11.2 - 28	118 A6	W 10	W 9	284	1205	565	3543	575	HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
 R1	 A6		
			

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

	SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
			REC RIM	ALT RIM						
										
	18.4 - 28	138 A6	W 16 L	W 15 L	467	1501	691	4413	-	STD
Ø30"	18.4 - 30	149 A6	W 16 L	W 15 L	460	1545	697	4712	725	STD
	23.1 - 30	164 A6	DW 20 B DW 20 A	-	600	1700	773	5217	-	DB
	18.4 - 30	154 A6	W 16 L	W 15 L	460	1545	697	4712	725	STD
	18.4 - 30	151 A6	W 16 L	W 15 L	460	1545	697	4712	725	STD
	9.5 - 30	109 A6	W 8	W 7	241	1200	567	3528	-	STD
	16.9 - 30	139 A6	W 15 L	W 14 L	429	1485	678	4535	700	STD
	23.1 - 30	155 A6	DW 20 B DW 20 A	-	600	1700	798	5046	-	STD
	16.9 - 30 (14 - 30)	146 A6	W 15 L	W 14 L	429	1485	678	4535	700	STD
	23.1 - 30	155 A6	DW 20 B DW 20 A	-	600	1700	773	5217	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index
			

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
9.5 - 30	115 A6	W 8	W 7	241	1200	567	3528	-	STD
18.4 - 30	145 A6	W 16 L	W 15 L	460	1545	697	4712	725	STD
14.9 - 30	131 A6	W 13	W 11 W 12	378	1415	659	4316	675	STD
18.4 - 30	145 A6	W 16 L	W 15 L	460	1545	697	4712	725	HD
23.1 - 30	146 A6	DW 20 B DW 20 A	-	600	1700	773	5217	-	STD
18.4 - 30	149 A6	W 16 L	W 15 L	460	1545	697	4712	725	STD
18.4 - 30	139 A6	W 16 L	W 15 L	460	1545	697	4712	725	STD
23.1 - 30	146 A6	DW 20 B DW 20 A	-	600	1700	773	5217	-	STD
18.4 - 30	149 A6	W 16 L	W 15 L	460	1545	697	4712	725	HD
7.2 - 30	95 A6	W 6	-	185	1095	523	3219	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
18.4 - 30	145 A6	W 16 L	W 15 L	460	1545	697	4712	725	HD
16.9 - 30	137 A6	W 15 L	W 14 L	429	1485	678	4535	700	STD
15 - 30 (18.4 - 30)	151 A6	W 16 L	W 15 L	460	1545	714	4542	725	STD
16.9 - 30 (14 - 30)	149 A6	W 15 L	W 14 L	429	1485	678	4535	700	STD
15 - 30 (18.4 - 30)	149 A6	W 16 L	W 15 L	460	1545	714	4542	725	STD
18.4 - 30	139 A6	W 16 L	W 15 L	460	1545	697	4712	725	HD
23.1 - 30	155 A6	DW 20 B DW 20 A	-	600	1700	773	5217	-	DB
23.1 - 30	164 A6	DW 20 B DW 20 A	-	600	1700	773	5217	-	DB
Ø32"	12.4 - 32	124 A6	W 11 W 9 W 10	325	1360	639	3998	650	STD
	12.4 - 32	124 A6	W 11 W 9 W 10	325	1360	639	3998	650	HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
			
Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index			

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
12.4 - 32	128 A6	W 11	W 9 W 10	325	1360	639	3998	650	HD
8.3 - 32	111 A6	W 7	W 6	211	1195	572	3585	-	STD
8.3 - 32	105 A6	W 7	W 6	211	1195	572	3585	-	STD
9.5 - 32	110 A6	W 8	W 7	235	1255	594	3686	-	STD
12.4 - 32	119 A6	W 11	W 9 W 10	325	1360	639	3998	650	STD
11.2 - 32	120 A6	W 10	W 9	287	1310	615	4007	-	HD
16.9 - 34	142 A6	W 15 L	W 14 L	429	1585	728	4794	750	HD
18.4 - 34	151 A6	W 16 L	W 15 L	467	1650	751	5009	775	STD
18.4 - 34	146 A6	W 16 L	W 15 L	467	1650	751	5009	775	HD
23.1 - 34	153 A6	DW 20 B DW 20 A	-	585	1810	834	5321	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
18.4 - 34	154 A6	W 16 L	W 15 L	467	1650	751	5009	775	HD
18.4 - 34	154 A6	W 16 L	W 15 L	467	1650	751	5009	775	STD
16.9 - 34	144 A6	W 15 L	W 14 L	429	1585	728	4794	750	HD
16.9 - 34	144 A6	W 15 L	W 14 L	429	1585	728	4794	750	STD
16.9 - 34	142 A6	W 15 L	W 14 L	429	1585	728	4794	750	STD
18.4 - 34	142 A6	W 16 L	W 15 L	467	1650	751	5009	775	STD
16.9 - 34	139 A6	W 15 L	W 14 L	429	1585	728	4794	750	HD
16.9 - 34	139 A6	W 15 L	W 14 L	429	1585	728	4794	750	STD
18.4 - 34	151 A6	W 16 L	W 15 L	467	1650	751	5009	775	HD SPL
18.4 - 34	137 A6	W 16 L	W 15 L	467	1650	751	5009	775	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
 R1  A6	 168 kg		Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Baikrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
18.4 - 34	151 A6	W 16 L	W 15 L	467	1650	751	5009	775	HD
23.1 - 34	153 A6	DW 20 B DW 20 A	-	585	1810	834	5321	-	STD
18.4 - 34	142 A6	W 16 L	W 15 L	467	1650	732	4860	775	HD
16.9 - 34	142 A6	W 15 L	W 14 L	429	1585	728	4794	750	HD
18.4 - 34	146 A6	W 16 L	W 15 L	467	1650	751	5009	775	STD
Ø36"	13.6 - 36	W 12	W 11	345	1515	713	4687	725	STD
	12.4 - 36	W 11	W 9 W 10	325	1465	696	4546	700	HD
	12.4 - 36	W 11	W 9 W 10	325	1465	696	4546	700	HD
	13.6 - 36	W 12	W 11	345	1515	713	4687	725	HD
	12.4 - 36	W 11	W 9 W 10	325	1465	696	4546	700	HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: 0.0. 2%—S.W. 2%—RC 2.5%—LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
12.4 - 36	131 A6	W 11	W 9 W 10	325	1465	696	4546	700	STD
12.4 - 36	135 A6	W 11	W 9 W 10	325	1465	687	4558	700	HD
9.5 - 36	122 A6	W 8	W 7	235	1360	646	4000	-	STD
12.4 - 36	126 A6	W 11	W 9 W 10	325	1465	696	4546	700	STD
12.4 - 36	139 A6	W 11	W 9 W 10	325	1465	696	4546	700	HD
8.3 - 36	107 A6	W 7	W 6	211	1295	628	4028	-	STD
13.6 - 36	125 A6	W 12	W 11	345	1515	713	4687	725	STD
8.3 - 36	113 A6	W 7	W 6	211	1295	628	4028	-	STD
13.6 - 36	129 A6	W 12	W 11	345	1515	712	4687	725	STD
12.4 - 36	135 A6	W 11	W 9 W 10	325	1465	696	4546	700	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

	SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
			REC RIM	ALT RIM						
										
NEW	12.4 - 36	139 A6	W 11	W 9 W 10	325	1465	696	4546	700	STD
	11.2 - 36	130 A6	W 10	W 9	290	1430			-	HD
Ø38"	13.6 - 38 (14.00 - 38)	139 A6	W 12	W 11	355	1565	735	4832	750	STD
	15.5 - 38	133 A6	W 14 L	-	395	1585	746	4660	-	STD
	15.5 - 38	138 A6	W 14 L	-	395	1585	746	4660	-	STD
	15.5 - 38	141 A6	W 14 L	-	395	1585	746	4660	-	STD
	18.4 - 38	153 A6	W 16 L	W 15 L	467	1750	794	5366	825	HD
	18.4 - 38	148 A6	W 16 L	W 15 L	467	1750	794	5366	825	HD
	20.8 - 38	166 A6	W 18 L	W 16 L	530	1835	846	5684	875	DB HD
	15.5 - 38	133 A6	W 14 L	-	395	1585	734	4748	-	HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
16.9 - 38	143 A6	W 15 L	W 14 L	429	1685	788	4954	800	STD
20.8 - 38	156 A6	W 18 L	W 16 L	530	1835	846	5684	875	HD
15.5 - 38	133 A6	W 14 L	-	395	1585	746	4660	-	HD
11.2 - 38	117 A6	W 10	W 9	284	1460	686	4409	-	STD
13.6 - 38 (14.00 - 38)	131 A6	W 12	W 11	345	1565	735	4832	750	STD
20.8 - 38	148 A6	W 18 L	W 16 L	530	1835	846	5684	875	STD
13.6 - 38 (14.00 - 38)	142 A6	W 12	W 11	345	1565	735	4832	750	STD
16.9 - 38	141 A6	W 15 L	W 14 L	429	1685	788	4954	800	HD
14.00 - 38 (13.6 - 38)	131 A6	W 12	W 11	345	1565	735	4832	750	STD
20.8 - 38	166 A6	W 18 L	W 16 L	530	1835	846	5684	875	DB HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
18.4 - 38	143 A6	W 16 L	W 15 L	467	1750	794	5366	825	HD
13.6 - 38 (14.00 - 38)	131 A6	W 12	W 11	345	1565	735	4832	750	HD
12.4 - 38	127 A6	W 11	W 9 W 10	325	1525	718	4670	-	STD
16.9 - 38	143 A6	W 15 L	W 14 L	429	1685	788	4954	800	HD
20.8 - 38	160 A6	W 18 L	W 16 L	530	1835	846	5684	875	STD
15.5 - 38	138 A6	W 14 L	-	395	1585	746	4760	-	HD
13.6 - 38 (14.00 - 38)	139 A6	W 12	W 11	345	1565	735	4832	750	HD
20.8 - 38	156 A6	W 18 L	W 16 L	530	1835	846	5684	875	STD
20.8 - 38	163 A6	W 18 L	W 16 L	530	1835	846	5684	875	DB HD
12.4 - 38	138 A6	W 11	W 9 W 10	325	1525	718	4670	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
14.00 - 38 (13.6 - 38)	139 A6	W 12	W 11	345	1565	735	4832	750	SPL
18.4 - 38	148 A6	W 16 L	W 15 L	467	1750	794	5366	825	HD
18.4 - 38	155 A6	W 16 L	W 15 L	467	1750	794	5366	825	STD
18.4 - 38	153 A6	W 16 L	W 15 L	467	1750	794	5366	825	STD
16.9 - 38	146 A6	W 15 L	W 14 L	429	1685	788	4954	800	STD
16.9 - 38	141 A6	W 15 L	W 14 L	429	1685	788	4954	800	STD
20.8 - 38	156 A6	W 18 L	W 16 L	530	1835	846	5684	875	STD
18.4 - 38	143 A6	W 16 L	W 15 L	467	1750	794	5366	825	STD
12.4 - 38	138 A6	W 11	W 9 W 10	325	1525	718	4670	-	STD
18.4 - 38	153 A6	W 16 L	W 15 L	467	1750	794	5366	825	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

	SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
			REC RIM	ALT RIM						
										
Ø42"	20.8 - 42	168 A6	W 18 L	W 16 L	535	1950	909	5733	-	DB HD
	20.8 - 42 (42)	158 A6	W 18 L	W 16 L	535	1950	909	5733	-	STD
	12.4 - 42	134 A6	W 10 W 10 A	-	322	1630	770	5011	-	STD
	20.8 - 42	158 A6	W 18 L	W 16 L	535	1950	909	5733	-	STD
	20.8 - 42	165 A6	W 18 L	W 16 L	535	1950	909	5733	-	STD
	9.5 - 42	125 A6	W 8	W 7	246	1510	721	4663	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
 R1	 A6		
			

Permissible tolerances: 0.0. 2%—S.W. 2%—RC 2.5%—LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index