

EARTHMAX SR 55



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 55

EARTHMAX SR 55 is an All Steel Radial tyre specially designed for loaders and load haul dumps operating in the most severe underground mining operations, and at scrapyards. Thanks to excellent cut protection resulting from the extra-deep and smooth tread design, EARTHMAX SR 55 is able to achieve peak productivity with reduced downtime along with excellent durability. Equipment operators will also appreciate extraordinary stability.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø24"	12.00 R 24	TT	L5S	**	175 A2	8.50/1.3	8.0 9.0	0	305	1274	572	3787	58	CR
	12.00 R 24	TL	L5S	**	175 A2	8.50/1.3	8.0 9.0	0	305	1274	572	3787	58	CR
Ø25"	29.5 R 25	TL	L5S	**	216 A2	25.00/3.5	-	0	777	1912	860	5755	104	CR
	26.5 R 25	TL	L5S	**	209 A2	22.00/3.0	-	0	690	1786	810	5375	95	CR

CR: CUT RESISTANT COMPOUND

TECHNOLOGIES					PERFORMANCES			
								

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
	18.00 R 25	TL	L5S	***	206 A2	13.00/2.5	-	0	513	1667	733	4852	86	CR
	26.5 R 25	TL	L5S	***	214 A2	22.00/3.0	-	0	690	1786	810	5375	95	CR
	20.5 R 25	TL	L5S	**	193 A2	17.00/2.0	-	0	535	1543	700	4644	74	CR
	18.00 R 25	TL	L5S	**	204 A2	13.00/2.5	-	0	513	1667	733	4852	86	CR
	17.5 R 25	TL	L5S	**	182 A2	14.00/1.5	-	0	453	1399	630	4211	68	CR
	17.5 R 25	TL	L5S	***	188 A2	14.00/1.5	-	0	453	1399	630	4211	68	CR
Ø29"	29.5 R 29	TL	L5S	***	223 A2	25.00/3.5	24.00/3.5 26.00/3.5	0	775	2009	911	6047	104	CR
	29.5 R 29	TL	L5S	**	218 A2	25.00/3.5	24.00/3.5 26.00/3.5	0	775	2009	911	6047	104	CR
Ø33"	35/65 R33	TL	L5S	**	224 A2	28.00/3.5	--	0	900	2065	915	6175	99	CR

CR: CUT RESISTANT COMPOUND

TECHNOLOGIES				PERFORMANCES			
							
L5S							
A2							
229 kg							

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. BKT reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
					REC RIM	ALT RIM							
													
35/65 R33	TL	L5S	***	229 A2	28.00/3.5	--	0	900	2065	915	6175	99	CR

CR: CUT RESISTANT COMPOUND



TECHNOLOGIES				PERFORMANCES			
							
							

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. BKT reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026