


# AGRIMAX V- FLECTO



<b>TIRE SIZE</b>	<b>VF 520/85 R 42</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATOR DE ALTA POTENCIA / TRATOR
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	180 D

## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	535	<b>RIM REC</b>	DW 18 L
<b>OD (MM)</b>	1951	<b>ECE</b>	E11-106R-007169
<b>SLR (MM)</b>	876	<b>SRI</b>	925
<b>RC (MM)</b>	5841	<b>TRA CODE</b>	R1W

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1	1.2	1.4	1.6	2	2.4	3.2
70	2840	3350	3860	4300	4805	5245	5755	6190	7280
<b>FROM 65 TO 40</b>	3120	3680	4240	4720	5280	5760	6320	6800	8000
30	3185	3755	4325	4815	5390	5880	6450	6940	8160
20	3245	3830	4410	4910	5495	5995	6575	7075	8320
10	3435	4050	4665	5195	5810	6340	6955	7480	8800
<b>UPTO 10 CYC WITH FRONT LOADER</b>	4370	5155	5940	6610	7395	8065	8850	9520	11200
10HT	3185	3755	4325	4815	5390	5880	6450	6940	8160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.