


# RIDEMAX IT 696

<b>TIRE SIZE</b>	<b>340/80 R 18 IND</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	143 A8 ; 138 D



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	343	<b>RIM REC</b>	11; 11 SDC; W 11
<b>OD (MM)</b>	1001	<b>RIM ALT</b>	W 10; 12; 12 SDC
<b>SLR (MM)</b>	458	<b>ECE</b>	E11-106R-002987
<b>RC (MM)</b>	2980	<b>SRI</b>	475

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.6	2.0	2.4	2.8	3.2	3.5	4.0
65	920	1135	1345	1535	1745	1960	2100	2360
50	995	1225	1455	1660	1885	2115	2270	2550
40	1065	1310	1555	1770	2015	2260	2425	2725
30	1110	1365	1620	1845	2100	2355	2525	2835

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.